

## Simplifying Ownership

**HIGHLY EFFICIENT.** IPSO's Horizon<sup>®</sup> front load washer keeps water use to an ultra-low 14.8 gallons per cycle, which can help your laundry reduce expenses. In addition, the washer's low water use qualifies it as an ENERGY STAR<sup>®</sup> product.

**SUPERIOR AIRFLOW.** IPSO small dryers produce fast-drying results with their advanced airflow pattern. Owners benefit from greater efficiency. But the real benefit comes from faster customer turnover and, as a result, greater profit potential.

**LARGE CAPACITY.** Our front load washer's 2.84 cu. ft. basket delivers the sizable capacity customers appreciate, which makes it a real profit producer for owners. Likewise, the matching dryer boasts a 7.0 cu. ft. cylinder.

**SPACE SAVINGS.** Choosing an IPSO stacked washer-dryer unit gives you a full capacity washer and dryer in the space of just one machine.

**GREAT SECURITY.** IPSO's washers and dryers are equipped with a cutting-edge electronic coin drop for added security. This drop uses signature recognition technology for superior coin validation.

**WORRY-FREE PERFORMANCE.** Our commitment to you comes with a 3-year parts warranty. Gravity drain available on select models.



## Simplifying Customer Satisfaction

**LARGE CAPACITY.** With an 18 lb capacity, IPSO's front load washer is ready to handle your customers' largest loads efficiently, while delivering excellent wash quality.

**SIMPLE CONTROLS.** Starting both the Horizon<sup>®</sup> and matching dryer is simple. Customers need only select one of four cycle options and hit start. A cycle time countdown and LEDs keep them apprised of the cycle progress.

**EASY LOADING.** A 188.6 sq. in. door opening on the washer and 2.06 sq. ft. opening on the dryer are huge assets for customers seeking to load and unload quickly.

**THE BOTTOM LINE.** Customers come to your laundry with one goal: to get in and out quickly. IPSO washers and dryers give them the means to do just that, increasing your profit potential.



BFNBCF, BDEBCF,  
BDGBCF, BTEBCF,  
BTGBCF



# Commercial Front Load Family Specifications

|                                  | <b>BFNBCF - Washer</b>                 |           | <b>BDGBCF - Gas Dryer</b><br><b>BDEBCF - Electric Dryer</b> |          | <b>BTGBCF - Stack Washer/Gas Dryer</b><br><b>BTEBCF - Stack Washer/Elec. Dryer</b> |          |
|----------------------------------|--|-----------|---|----------|--|----------|
| Height - in (mm)                 | 43" (1092)                             |           | 43" (1092)  |          | 76 1/2" (1943)   |          |
| Width - in (mm)                  | 26 7/8" (683)                          |           | 26 7/8" (683)   |          | 26 7/8" (683)  |          |
| Depth - in (mm)                  | 28" (711)                              |           | 28" (711)   |          | 28" (711)  |          |
| Work Surface Height - in (mm)    | 43" (1092)                             |           | 43" (1092)  |          | N/A  |          |
| Water Temperatures               | Hot, Warm, Cold                        |           | N/A   |          | Hot, Warm, Cold  |          |
| Cycles                           | Heavy, Normal, Perm Press and Delicate |           | High Temp, Med Temp, Low Temp, Delicates                    |          | (Same as single washer & dryer)  |          |
| Basket Volume - cu. ft. (bar)    | 2.84 (80)                              |           | 7.0 (198)   |          | 7.0 (198)  |          |
| Water Pressure - psi (bar)       | Pressure fill - 20 to 120 (1.4/8.3)    |           | N/A   |          | Pressure fill - 20 to 120 (1.4/8.3)  |          |
| Spin Speed - RPM                 | 1000, 650, 500                         |           | N/A   |          | 1000, 650, 500   |          |
| Control(s)                       | Coin Electronic                        |           | Coin Electronic   |          | Coin Electronic  |          |
| Motor - HP                       | 1                                      |           | 1/3   |          | 1, 1/3   |          |
| Motor - RPM                      | Variable Speed                         |           | 1725  |          | Variable Speed, 1725   |          |
| Voltage/Hz/Phase Circuit Breaker | Gas: N/A<br>Electric: 120/60/1         | N/A<br>15 | Gas: 120/60/1<br>Electric*: 120/240/60/1                    | 15<br>30 | Gas: 120/60/1<br>Electric*: 120/240/60/1   | 15<br>30 |
| Top Finish                       | Porcelain                              |           | Porcelain   |          | N/A  |          |
| Colors                           | White, Stainless Steel                 |           | White, Stainless Steel                                      |          | White  |          |
| Net Weight - lb (kg)             | 250 (113)                              |           | Gas: 155 (70), Electric: 150 (68)                           |          | Gas: 365 (166), Electric: 360 (163)  |          |
| Crated Weight - lb (kg)          | 270 (123)                              |           | Gas: 165 (75), Electric: 160 (73)                           |          | Gas: 395 (179), Electric: 390 (177)  |          |
| Agency Approvals                 | cUL <sub>US</sub>                      |           | Gas: CSA Star, CSA Flame<br>Electric: cUL <sub>US</sub>     |          | Gas: CSA Star, CSA Flame<br>Electric: cUL <sub>US</sub>                            |          |

\* Factory equipped 120/240/60/1 - may be field converted to 120/208/60/1 by qualified servicer.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2011 Alliance Laundry Systems LLC

Printed in the U.S.A.

Questions? Contact us at:  
1 800 USA IPSO or www.ipso.com  
1 800 (872-4776)

## Control Options



**Washer Control**



**Dryer Control**



**Stack Washer/Dryer Control**