



Stack tumble dryers

DR335 - DR445

Features

- Double capacity in same floor space
- Extra large cylinder capacity
- Large door opening for easy loading and unloading
- Standard galvanized drum
 - oval drum holes preventing damage from standard drywall screws
- Unique suspension system
 - at the rear: bearing
 - at the front: rubber rolls with bearings
- Large lint filter
 - easy removal of lint
 - efficient drying
 - self cleaning filter
- Axial airflow
 - drum perforations only at the front and back
 - maximum airflow, less energy consumption and short drying times
- DX4 control
 - easy to use and flexible microprocessor control
 - 3 freely adaptable programs
 - temperature can be freely programmed per degree, drying and cool-down times easily programmable

Options

- OPTimum control (over-dry prevention technology)
 - easy to operate, easy to program
 - 30 programmable cycles



- 3 cycle types
 - . Time Dry: programmable time and temperature
 - . Auto Dry: 11 programmable automatic dryness levels and programmable temperature
 - . Moisture Dry: will dry to the programmed moisture level at programmed temperature
- Coin-operated version for vended laundry applications

	DR335	DR445
Capacity 25:1	2 x 12 kg	2 x 16,8 kg
Capacity 20:1	2 x 15 kg	2 x 21 kg
Drum		
Volume	301 l	2 x 421 l
Diameter	762 mm	838 mm
Depth	660 mm	762 mm
Door opening diameter	576 mm	683 mm
Temperature min	38 °C	38 °C
Temperature max	88 °C	88 °C
Power motor non-reversing		
Drum	0,19 kW	0,37 kW
Fan	0,19 kW	0,37 kW
Exhaust flow rate (50hz)	160 l/s	236 l/s
Diameter	203 mm (**)	254 mm
Power		
Electric heating	2 x 21 kW	-
Gas heating	73.000 Btu/h	87.000 Btu/h
Gas heating	18.390 kcal	21.924 kcal
Steam heating		
@ 6,9 Bar	111.000 Btu/h - 32,5 kW	-
@ 1,0 Bar	74.000 Btu/h - 21,7 kW	-
Steam connection inlet	3/4"	-
Steam connection outlet	3/4"	-
Gas connection	1/2" (**)	1/2" (**)
Gas connection - pressure ng/lp	20 / 28,37 mb	-
Noise level	66 dBA	67 dBA
Transport data		
Net weight	247 kg	305 kg
Gross weight	264 kg	326 kg
Packing dimensions HxWxD	2057x825x1194 mm	2159x902x1372 mm
Available controls		
DX4 (coin or OPL)	standard	standard
OPTimum (OPL only)	optional	optional

(**) Single gas inlet & elliptical exhaust

