



DRYER

FOR SEMI-COMMERCIAL LAUNDRY APPLICATIONS (OPL)

INDUSTRIAL
BY DESIGN

Dependable & Efficient

- Superior Airflow
 - » Advanced blower system produces airflow of 220 cu. Ft. per minut
 - » Fast-drying results with advanced airflow pattern
 - » Minimum Dry times
- Large Capacity
 - » Large 7.0 ct. ft. cylinder
- Door opening of 2.06 sq. ft. for fast and easy loading and unloading
- Time Savings
 - » Large, easy-clean lint filter is located upfront


Control

- Electronic Homestyle Control (Front)
 - » Digital display
 - » Six preset cycle options
 - » Customizable cycles
 - » Cycle time countdown
 - » LED progress indicators
- Electromechanical Control (Rear)
 - » Mechanical interface
 - » Easy operation
 - » Basic fabric selections
 - » Cycle time: user adjustable



DRYER

Specifications	Front Control	Rear Control
Available Controls	Electronic Homestyle	Emech
Capacity - lb (kg)	18 (8.2)	18 (8.2)
Cylinder Volume - cu. Ft. (liters)	7.0 (198)	7.0 (198)
Width - in (mm)	26 7/8 (683)	26 7/8 (683)
Depth - in (mm)	28 (711)	28 (711)
Height - in (mm)	40 7/16 (1027)	43 (1092)
Motor Size - HP (kw)	1/3 (0.25)	1/3 (0.25)
Available Heat Sources	Gas or Electric	Gas or Electric
Available Heating Element (Electric W)	4750 @ 208V 5350 @ 240V	4750 @ 208V 5350 @ 240V
Gas Inlet Connection - in (mm)	3/8 (9.5)	3/8 (9.5)
Gas Consumption - BTU/Hr	22,500	22,500
Exhaust Outlet Diameter - in (mm)	4 (102)	4 (102)
Exhaust Airflow - cfm (liters/sec)	220 (105)	220 (105)
Available Cycles	Regular, Perm Press, Delicate, Time Dry, Quick Dry, Fluff Up	Normal, Casual, Delicate, No Heat
Cycle Indicator Lights	Yes	Yes
Cylinder Finish	Galvanized	Galvanized
Available Colors	White	White
Door Type (Solid/Window)	Solid	Solid
Available Electrical Requirements - (Voltage/Hz/Ph)	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp	Gas: 120/60/1 - 15 Amp Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp
Net Weight - lb (kg)	Elec/Gas 145/150 (66/68)	Elec/Gas 130/135 (59/61)
Shipping Weight - lb (kg)	Elec/Gas 155/160 (70/73)	Elec/Gas 140/145 (64/66)
Shipping Dimensions		
Width - in (mm)	29 (737)	29 (737)
Depth - in (mm)	32 3/4 (832)	32 3/4 (832)
Height - in (mm)	45 1/2 (1156)	45 1/2 (1156)
Available Agency Approvals	Elec: cUL _{US} , Gas: cCSA _{US}	Elec: cUL _{US} , Gas: cCSA _{US}



Note: Not all options are available for all models. Refer to the price list for the available models and options.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

©Copyright 2015 Alliance Laundry Systems LLC

Alliance Laundry Systems LLC
Shepard Street
Ripon, WI 54971